



## CEILING LED LAMP OPAL

### CEILING LED LAMP OPAL DL-110-0380-4064

The lamps are mounted directly on the support surface.  
The method of attachment of the invoice. Fasteners are included in the delivery package. Plastic housing, diffuser made of polypropylene. The lamp is not dimmed.

#### Product data

##### General information

Beam angle of light	120 °
source Light source	cold white
colour	No
Light source replaceable	No
Driver included	-
Control interface	-

Cable

##### Operating and electrical

Input Voltage	175 to 250 V
Input frequency	50 or 60 Hz
Initial CLO power consumption	40 W
Average CLO power consumption	- W
Inrush current	20 A
Inrush time	0.04 ms
Power factor (min.)	0.9

Glow-wire test Temperature 850 °C, duration 30 s

##### Initial performance (IEC compliant)

Initial luminous flux	3600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	80 lm/W
Init. Corr. Colour Temperature	6400 K
Init. Colour rendering index	>80
Initial chromaticity	40 W
Power consumption tolerance	+/-10%

##### Application conditions

Ambient temperature range	-20 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	Not applicable
Suitable for random switching	Not applicable

# BUILT-IN SATURN LAMPS

## Mechanical and housing

Housing material	PP
Reflector material	-
Optic material	PP
Optical cover/lens material	PP
Fixation material	-
Overall height	35 mm
Overall diameter	370 mm


## Approval and application

Ingress protection code	IP65
-------------------------	------

## Product data

Full product code	4870241040990
Order product name	DL-110-0380-4064
SAP numerator – quantity per pack	1
Numerator – packs per outer box	20

## Dimensional drawing



DL-110-0380-4064