



LED LAMP SERIES LPB

LED LAMP SERIES LPB DL-179-6400-020

LED DPB oval- LED energy-saving dust- and moisture-proof. They have a degree of protection from dust and moisture IP54 and can be used in rooms with a high dust and moisture content. The lamp has shockproof properties.

Product data

General information

Beam angle of light source	120 °
Light source colour	cold white
Light source replaceable	No
Driver included	No
Control interface	-
Cable	-

Operating and electrical

Input Voltage	165 to 265 V
Input frequency	50 or 60 Hz
Initial CLO power consumption	20 W
Average CLO power consumption	- W
Inrush current	20 A
Inrush time	0.04 ms
Power factor (min.)	0.9

Glow-wire test	Temperature 850 °C, duration 30 s
----------------	-----------------------------------

Initial performance (IEC compliant)

Initial luminous flux	1500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	80 lm/W
Init. Corr. Colour Temperature	6400 K
Init. Colour rendering index	>80
Initial chromaticity	20 W
Power consumption tolerance	+/-10%

Application conditions

Ambient temperature range	-20 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	Not applicable
Suitable for random switching	Not applicable

BUILT-IN SATURN LAMPS

Mechanical and housing

Housing material	Polycarbonate
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Overall height	60 mm
Overall diameter	165 mm


Product data

Full product code	4870241040150
Order product name	DL-179-6400-020
SAP numerator – quantity per pack	1
Numerator – packs per outer box	50

Approval and application

Ingress protection code	IP54
-------------------------	------

Dimensional drawing



DL-179-6400-020