

DEUTSCHER

E L E C T R I C 



LED DKU MAIN

Main console lamps

The DKU MAIN LED lamp is designed to illuminate streets, roads with medium and low traffic intensity, squares, parking lots, railway platforms, courtyards, squares in front of shopping centers.

Features and Benefits

- Reliable quality assurance without problems for external use
- DRIVER WITH WATERPROOF INSULATION
- Energy saving

Specifications

Family	Main console lamps			
View	DKU MAIN			
System light output*	9100Lm	13000Lm	19500Lm	26000Lm
Power	70W	100W	150W	200W
Power Factor	>0.97			
Angle	SWB(110°)			
CCT	6500K(CW)			
Temperature regime	-40°C ~ +40°C			
Service life	10,000 hours			
IP class	IP65			
Input voltage	220-240V~, 50/60Hz			
Approbation	EAC			

Размер

Type	Power	Height	Width	Thickness
DKU MAIN	70W	402	127	60
	100W	462	142	66
	150 W	532	172	75
	200 W	532	172	75

LED ДКУ DRIVE 70W 9100Lm 402x127x60 6500K IP65 (DEUTSCHER)	DL-XX-6500-070
LED ДКУ DRIVE 100W 13000Lm 462x142x66 6500K IP65 (DEUTSCHER)	DL-XX-6500-100
LED ДКУ DRIVE 150W 19500Lm 532x172x75 6500K IP65 (DEUTSCHER)	DL-XX-6500-150
LED ДКУ DRIVE 200W 26000Lm 532x172x75 6500K IP65 (DEUTSCHER)	DL-XX-6500-200