



# LEDER LED FLOODLIGHTS

# LEADER LED FLOODLIGHTS DLFDW-300-64

The LEADER LED series of luminaires is designed for architectural and functional lighting. The design of the lamp allows you to place it both on the facades of buildings and on industrial sites. A wide range of capacities and optical systems makes this spotlight a universal solution for the most complex outdoor lighting projects.

#### Product data

#### General information

Light source color	Cold white
Driver included	No
Optical cover/lens type	Polycarbonate bowl/cover
Operating and electrical	
Input Voltage	175 to 265 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.95
Luminous flux tolerance Initial LED luminaire efficacy	+/-10% 100 lm/W
Init. Corr. Color Temperature	6400 K
Init. Color Rendering Index	>80
Initial input power	300 W
Power consumption tolerance	+/-10%

#### Mechanical and housing

Housing Material	Aluminum
Overall length	290 mm
Overall width	395 mm
Overall height	48 mm
Color	Black

#### Approval and application

Ingress protection code IP65

#### Initial performance

Initial luminous flux 24300lm

## **KRAFT LED FLOODLIGHTS**

### Application conditions

Ambient temperature range -40 to +45 °C


\_\_\_\_\_\_

Product data

Full product code 4870241042475

# Order product name Numerator - Quantity Per Pack Numerator - Packs per outer box 5

# Dimensional drawing



DLFDW-300-64