DEUTSCHER

## ELECTRIC =



# LEDER LED FLOODLIGHTS

## LEADER LED FLOODLIGHTS DLFDW-400-64

The LEADER LED series of luminaires is designed for architectural and functional lighting. The design of the lamp allows you to place it both on the facades of buildings and on industrial sites. A wide range of capacities and optical systems makes this spotlight a universal solution for the most complex outdoor lighting projects.

#### Product data

#### General information

Light source color	Cold white		
Driver included	No		
Optical cover/lens type	Polycarbonate bowl/cover	Mechanical and housing	
		Housing Material	Aluminum
Operating and electrical		Overall length	337 mm
Input Voltage	175 to 265 V	Overall width	457 mm
Input Frequency	50 or 60 Hz	Overall height	48 mm
Power Factor (Min)	0.95	Color	Black
Luminous flux tolerance	+/-10%		
Initial LED luminaire efficacy	100 lm/W	Approval and application	
Init. Corr. Color Temperature	6400 K	Ingress protection code	IP65
Init. Color Rendering Index	>80		
Initial input power	400 W	Initial performance	
Power consumption tolerance	+/-10%	Initial luminous flux	32400lm

### **KRAFT LED FLOODLIGHTS**

-40 to +45 °C

4870241042482

#### Application conditions


Ambient temperature range

DLFDW-400-64 Order product name Numerator - Quantity Per Pack 1 Numerator - Packs per outer box 4

#### Product data

Full product code

## Dimensional drawing



DLFDW-400-64