



CEILING LED LAMP OPAL

CEILING LED LAMP OPAL DL-116-0460-6064

The lamps are mounted directly on the support surface.
The method of attachment of the invoice. Fasteners are included in the delivery package. Plastic housing, diffuser made of polypropylene. The lamp is not dimmed.

Product data

General information

Beam angle of light	120 °
source Light source	cold white
colour	No
Light source replaceable	No
Driver included	-
Control interface	-

Cable

Operating and electrical

Input Voltage	175 to 250 V
Input frequency	50 or 60 Hz
Initial CLO power consumption	60 W
Average CLO power consumption	- W
Inrush current	20 A
Inrush time	0.04 ms
Power factor (min.)	0.9

Glow-wire test Temperature 850 °C, duration 30 s

Initial performance (IEC compliant)

Initial luminous flux	5400 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	80
Init. Corr. Colour Temperature	lm/W
Init. Colour rendering index	6000 K
Initial chromaticity	>80
Power consumption tolerance	60 W

Application conditions

Ambient temperature range	-20 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	Not applicable
Suitable for random switching	Not applicable

BUILT-IN SATURN LAMPS

Mechanical and housing

Housing material	PP
Reflector material	-
Optic material	PP
Optical cover/lens material	PP
Fixation material	-
Overall height	70 mm
Overall diameter	450 mm


Approval and application

Ingress protection code	IP65
-------------------------	------

Product data

Full product code	4870241042390
Order product name	DL-116-0460-6064
SAP numerator – quantity per pack	1
Numerator – packs per outer box	20

Dimensional drawing



DL-116-0460-6064